

EMEA Region

[Download Instructions \(multilingual\)](#)

Universal Charger

INNOVATIVE

- Unique and modern design
- Charges AA, AAA, C, D and 9V NiMH rechargeable batteries.



SMART

- LCD panel indicating charging status
- LED indicator for 9V



POWERFUL

- 3-5 hour charging time



Before Using Your Charger:

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Product Detail:

Designation: Universal Charger - European Region

Color: Black and Silver

Charging Current: 2 or 4 "AA-C-D" 650mA

2 or 4 "AAA" 400mA 1 or 2 "9V" 17mA

Trickle Charge: "AA-C-D" 50mA

"AAA" 25mA

| Charging Times: (estimated) | Battery (NiMH) | Capacity (mAh) | Estimated (time) |
|--------------------------------|-------------------|-------------------|---------------------|
| | AA | 2500-2650 | 4.5-5.0 hrs |
| | AA | 1700-2400 | 3.0-4.5 hrs |
| | AAA | 850-1000 | 2.5-3.0 hrs |
| | C/D | 2500 | 4.5 hrs |
| | 9V | 175 | 12.5 hrs |

Shutoff Mechanism: Delta V Detection and Timer Control

Delta V Detection 5mV per cell for "AA-AAA-C-D"

Max Timer Control 2 or 4 "AA-C-D" 5 hours

2 or 4 "AA" 3.5 hours

Charger Input : DC 12V, 600mA

AC Adapter Input: 100-240V AC 50/60Hz 190mA

AC Adapter Output: DC 12V, 600mA

Weight (charger): 322 grams

Dimensions (mm): 65 x 180 x 130 (H x L x W)

Safety Features*: Delta V Charging Cut Off

Short Circuit and Reverse Polarity Protection

Safety Timer to Prevent Over Charge

Bad Battery Detection

NOTE: Batteries must be charged in pairs with the exception of "9V" batteries that can be charged individually

* These features do not apply to "9V" batteries.

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer

Contents herein do not constitute a warranty.