# PRODUCT DATASHEET

# NiMH Battery Charger (CHPC)

# Dock & Go™ Charger

### **Asia Pacific Region Download Instructions**

#### **POWERFUL**

 Charges up to 8 NiMH AA's or AAA's in Pairs



#### HI-TECH

• 3 Step LED Charging Indicators (Red, Green, Amber)



#### **GLOBAL USE**

 Universal Voltage 100-240VAC 50/60 Hz



#### CONVENIENT

• 2 Portable Charging Pods Included – One for Home and One to



## **ADVANCED**

- Two Stage Charge
- Primary Battery Detection







#### **Before Using Your Charger:**

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

#### **Product Detail:**

**Designation**: Dock & Go<sup>™</sup> - Asia Pacific Region

Model: CHPC Color: Black and Silver

Charge Capability: "AA" (2) to (8) in pairs "AAA" (2) to (8) in pairs

> "AA" (2) and "AAA" (2) simultaneously "AA" (4) and "AAA" (4) simultaneously

Note: When charging only 2 batteries, place

batteries together on the left or right side

Charging Times: Battery Capacity Estimated (estimated) (NiMH) (mAh) (time) 1700-2400 1.8-2.8 hrs 2500-2650 2.8-3.0 hrs AAA 850-1000 2.5-3.0 hrs

**Shutoff Mechanism**: Timer (240 minutes ± 10 minutes)

Delta V Detection

Charging Current: (For POD 1 or POD 2 port)

"AA" 1000mA x 2 per channel "AAA" 400mA x 2 per channel

Top Off Charge: 55mA (4) hours

Adaptor Input Rating: 100-240VAC, 50/60Hz

Adaptor Input Power: 17W Charger Input Rating: 12VDC Typical Weight: 165 grams

(without batteries or adaptor)

Dimensions (mm): Pod: 71 x 76 x 23 (H x L x W)

Base: 86 x 69 x 25 (H x L x W)

**Rev Polarity Protection:** Yes Primary Battery Detection: Yes

#### **Important Notice**

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc.

Contents herein do not constitute a warranty.

