

North American Region

Download Instructions and Warranty Information

[English](#) | [Français](#) | [Español](#)



Product Detail:

Designation: Dock and Go

Model: CHPC **Color:** Black and Silver

Charge Capability: "AA" (2) to (8) in pairs
 "AAA" (2) to (8) in pairs
 "AA" (2) and "AAA" (2) simultaneously
 "AA" (4) and "AAA" (4) simultaneously

Note: When charging only 2 batteries, place batteries together on the left or right side

Battery (NiMH)	Capacity (mAh)	Estimated (time)
AA	1700-2400	1.8-2.8 hrs
AA	2500-2650	2.8-3.0 hrs
AAA	850-1000	2.5-3.0 hrs

Charging Times: (estimated)
Shutoff Mechanism: Timer (240 minutes ± 10 minutes)
 Delta V Detection

Charging Current: (For POD 1 or POD 2 port)
 "AA" 1000mA x 2 per channel
 "AAA" 400mA x 2 per channel

Top Off Charge: 55mA (4) hours

Adaptor Input Rating: 100-240VAC, 50/60Hz

Adaptor Input Power: 17W

Charger Input Rating: 12VDC

Typical Weight: 165 grams (5.3 oz.)

(without batteries or adaptor)

Dimensions (mm): Pod: 71 x 76 x 23 (H x L x W)

Base: 86 x 69 x 25 (H x L x W)

Rev Polarity Protection: Yes

Primary Battery Detection: Yes

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc.

Contents herein do not constitute a warranty.

Dock & Go™ Charger



Before Using Your Charger:

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with Energizer NiMH batteries.

POWERFUL

- Charges up to 8 NiMH AA's or AAA's in Pairs



HI-TECH

- 3 Step LED Charging Indicators (Red, Green, Amber)




GLOBAL USE

- Universal Voltage 100-240VAC 50/60 Hz



CONVENIENT

- 2 Portable Charging Pods Included – One for Home and One to Go



ADVANCED

- Two Stage Charge
- Primary Battery Detection

