# PRODUCT DATASHEET

# NiMH Battery Charger (CHQA)

### **European Region**

Download Instructions (multilingual)

Page 01 | Page 02 | Page 03

## Rapide Charger

### HI-TECH

· Red and Green LEDs for each pair of batteries show charging status and alert for bad batteries



#### CONVENIENT

 Charge 2 or 4 AA or AAA batteries at the same time



#### **ADVANCED**

- · Two Stage Charge
- Primary Battery Detection



#### **Before Using Your Charger:**

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

#### **Product Detail:**

**Designation:** Rapide Charger

Color: Black and Silver

Charging Current: 2 or 4 "AA" 600mA

2 or 4 "AAA" 350mA

Slow Charge: "AA" 350mA

"AAA" 175mA

Tric' & Charge: 0-70mA

b ging Times: (estimated)

:	Battery	Capacity	Estimated
)	(NiMH)	(mAh)	(time)
	AA	2500-2650	5.0-5.3 hrs
	AA	1300-2400	2.6-4.8 hrs
	AAA	850-1000	2.9-3.4 hrs

Shutoff Mechanism: Delta V and Temperature Detection

and Timer Control

Delta V Detection 0-15mV per channel (2 cells)

Temp. Detection 41-45°C

Max Timer Control 2 or 4 "AA" 6 hours

2 or 4 "AA" 3.5 hours

Charger Input: 100-240V AC 50/60Hz

Weight (charger): 138.8 grams

**Dimensions (mm):** 34.7 x 112.0 x 69.5 (H x L x W)

Safety Features: Delta V Charging Cut Off

Short Circuit and Reverse Polarity Protection

Safety Timer to Prevent Over Charge Primary and Bad Battery Detection

**NOTE:** Batteries must be charged in pairs.

#### **Important Notice**

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc.

Contents herein do not constitute a warranty.