PRODUCT DATASHEET

NiMH Battery Charger (CHUSB)

CONVENIENT

- flip top cover
- wrap around USB cord
- you can carry/store batteries in it

FAST

• Charges 2 AAA in 1.6 Hours (900 mAh) 2 AA in 5.5 Hours (2500 mAh)



EASY

- Plug the charger into the USB outlet
- Download charger software

INNOVATIVE

• Charger interface tells you how long it takes to charge the batteries and when the batteries are done charging



FUN

 2 Fun colors available Green Blue





USB Charger The Charger for the Millennial

For more information on the USB/computer interface visit www.energizer.eu/usbcharger

NOTE: The computer software is designed to monitor only one Energizer® USB charger at a time.



Before Using Your Charger:

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

European Region

Download Instructions (multilingual)

Page 01 | Page 02

Product Detail:

Designation: USB Charger

Color: Black and Green or Blue

Capabilities: 1 to 2 "AA" NOTE: When charging a single

1 to 2 "AAA" battery, use bay (1) only

Charging Current: USB Quick Charge 1-2 "AA-AAA" 550mA

USB Slow Charge 1-2 "AA-AAA" 125mA NOTE: Quick charge current depends on the power

output of the computer USB. Multiple devices using the USB ports will greatly reduce charge current to a slow charge. The AC adapter will always provide a

quick charge current.

Trickle Charge: 20-60mA

Shutoff Mechanism: Delta V, Max Voltage and Timer Control

Delta V Detection 10mV per cell Max Voltage 1.65V per cell

Max Timer Control Quick Charge "AA" 5.5 hours

Quick Charge "AAA" 1.5 hours Slow Charge "AA" No Timer Slow Charge "AAA" 10 hours

Charger Input: Quick Charge DC 5V 500mA

Slow Charge DC 5V 100mA

Weight (charger): 68 grams

Dimensions (mm): 33 x 101 x 40 (H x L x W) Safety Features: Delta V Charging Cut Off

> Max Voltage Shutoff Reverse Polarity Protection Primary Battery Detection

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc.

Contents herein do not constitute a warranty.