

1-800-383-7323 USA/CAN www.energizer.com

## **Miniature Alkaline**

Industry Standard Dimensions mm (inches)

6.10 (0.240)

5.60 (0.220)

15.50 (0.610)

15.00 (0.591)

13.20 (0.520)

13.00 (0.512)

**ENERGIZER E625G** 

Chemical System:


Designation: Nominal Voltage: Typical Capacity:

Typical Weight: Typical Volume: N/A 1.5 Volts 178 mAh (to 0.9 volts) Rated at 2.5K ohms / 21°C (70°F) 3.3 grams (0.12 ounces) 1.2 cubic centimeters (0.07 cubic inch)

## **Cross Section**

**Specifications** 

Manganese Dioxide (MnO<sub>2</sub>)



Designed specifically for photo use

(+)

# **Typical Discharge Characteristics**

21°C (70°F)

Load: 2.5K ohms - Continuous Typical Drain @ 1.25V: 0.5 mA



Schedule:	<b>Typical Drains:</b> at 1.25V (milliamperes)	Load (ohms)	Cutoff 0.9V (hours)
Continuous	0.5	2,500	356

### **Important Notice**

This data sheet contains typical information specific to products manufactured at the time of its publication. © Energizer Holdings, Inc. - Contents herein do not constitute a warranty.