

628909

European Region

INTRINSICALLY SAFE

- Approved by global agencies for intrinsically safe lights
- Division 1, Class 1 rated



WATERPROOF

- Meets IEC 60529 IPX7 standards – 1 m for 30 min



IMPACT RESISTANT

- Survives a 2-meter drop



RELIABLE

- 45 hour run time using Energizer® MAX® batteries



Approved by global safety agencies, the MS2DLED is ideal for work in harsh conditions. The light is waterproof, dustproof and survives a 2 meter drop test.

A built-in carabiner belt clip makes for easy access, while the internationally approved orange safety color provides instant recognition. The White LED lamp supplies steady, bright illumination for about 70 hours between battery changes.



- UL/CUL intrinsic safety for hazardous locations Class I Div. 1 Groups A,B,C, & D, Class II Div. 1 Groups E,F,&G, and Class III Div. 1; T4.
- MSHA for methane-air mixtures.
- ATEX intrinsically safe flashlight for IM2/II1G EEx ia I/IIIC T4
- IECEx intrinsically safe flashlight for Ex ia IIC T4
- -20°C to 40°C ambient operating range.
- 0539
- EN60529 ingress protection level IP67.


Before Using Your Flashlight:
Please read all instructions and cautionary markings on the package and light

European Region

Product Detail:

- Designation:** Energizer 2D ATEX
- SAP:** 628909
- Color:** Safety Orange and Black
- Power Source:** Two "D"
- IEC:** LR20
- Lamp:** One High Power LED
- Lamp Life (hr):** Lifetime
- Lamp Output (lumens):** 28
- Beam Distance (m):** 115
- Peak Beam Intensity (cd):** 3,306
- Run Time (h:mm):** 45
- Durability:** Survives 2-meter drop
- Typical Weight:** 162 grams without batteries
- Dimensions (mm):** 201.4 x 50.8 x 64.8

Performance:



Tested according to ANSI/NEMA FL 1 Standards.

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication
Contents herein do not constitute a warranty
©Energizer / All Rights Reserved