


ENERGIZER NO. E96

AAAA



Industry Standard Dimensions in mm (inches)



Chemical System: Alkaline
Zinc-Manganese Dioxide (Zn/MnO₂)
(No Added Mercury or Cadmium)

Designation: ANSI-25A

Battery Voltage: 1.5 Volts

Operating Temp: -18°C to 55°C (0°F to 130°F)

Average Capacity: 625 mAh (to 0.8 volts)
(Rated capacity at 25 mA continuous drain)

Average Weight: 6.5 grams (0.2 oz.)


Volume: 2.2 cubic centimeters (0.1 cubic inch)

Cell: One No. 3-0316 (size 'AAAA')


Jacket: Plastic Label

Shelf Life: 7 years (80% of rated capacity)


TEMPERATURE EFFECTS
Typical Service to 0.8 Volts



CONSTANT RESISTANCE PERFORMANCE
Typical Service



CONSTANT CURRENT DISCHARGE
Typical Service




Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.




Contents herein do not constitute a warranty.

Copyright © Eveready Battery Co. - All rights reserved

ENERGIZER NO. E96



ANSI - IEC Industry Standard Tests @ 20° C



Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.

Contents herein do not constitute a warranty.

Copyright © Eveready Battery Co. - All rights reserved